Technical Data Sheet

2/13/2015

Model: AEA5465EXD

Product Description

Type:	Reciprocating
Application:	HBP/AC - Air Conditioning
Refrigerant:	R-22
Voltage/Frequency:	208-230V ~ 60Hz 200V ~ 50Hz
Version:	N/A

Product Specifications

General

Evaporating Temp. Range:	-23.3°C to 12.8°C (-10°F to 55°F)
Motor Torque:	Low Start Torque (LST)
Compressor Cooling:	Fan

Mechanical

Weight:	25
Weight Unit of Measure:	LB
Displacement (cc):	12.045
Oil Type:	Synthetic Alkylate
Viscosity (cSt):	32
Oil Charge (cc):	296

Electrical

Voltage Range (50 Hz):	180-220
Voltage Range (60 Hz):	187-254
Locked Rotor Amps (LRA):	20
Rated Load Amps (RLA 50 Hz):	0
Rated Load Amps (RLA 60 Hz):	4
Max. Continuous Current (MCC in Amps):	0
Motor Resistance (Ohm) - Main:	3.02
Motor Resistance (Ohm) - Start:	8.63
Motor Type:	PSC
Overload Type:	N/A
Relay Type:	N/A

Agency Approval

cURus Recognized